

PRODUCTION TRAILER

SPECIFICATION



Our production trailer offers a flexible solution for increased gallery space or additional technical facilities on site

Working in combination with our production trucks it easily accommodates up to eight crew and includes separate areas for EVS, Graphics or other specialist operators.

With lighting, heating, air conditioning and plenty of desk space, the trailer also operates as an ideal production office space for crew on location.

Main Production Area

2 x 49" Sony LCD screens for vision mixer multi-viewer output
– Also fed by 2 x Decimator quad multi-viewers

2 x Genelec speakers with individual volume control for monitoring program sound

Dedicated EVS position with 2 x 19" LCD screens, comms panel and audio monitoring

Dedicated vision mixer desk position with desk cut out to fit the vision mixer panel – Includes dedicated KP32 RTS comms panel

3 other desk positions, all with RTS comms panels for PA, show caller or other production personnel

Removable desk panel connecting gallery desk & EVS position

Air conditioning and heating

Time code studio clock

Various mains sockets and patch cables for VTs, laptops, etc.

Spotlights and main strip lights

Perspex opening window to multi-purpose technical area

Capacity for additional desk & seating positions

Multi-purpose Technical Area

2 x 32" LCD screens

– 1 x screen dedicated to graphics, 1 x fed by quad multi-viewer

2 x Fostex speakers with individual volume controls

RTS comms panel aperture on desk

Various patch cables to CTP & rear of trailer

Perspex (opening) window to main production area

Various mains sockets

Spotlights & main strip lights



Telephone +44 (0)1279 630555
Email bookings@linksbroadcast.com
www.linksbroadcast.com



PRODUCTION TRAILER

SPECIFICATION

Rear Storage Area

Storage or additional technical area suitable for flight-cases, EVS, etc.

Mains Requirements

2 x 16amp inputs with technical equipment powered separately to general mains input

Dimensions

Length	5.5m Internal	7.0m overall
Width	2.2m internal	2.25m overall
		+0.75m clearance required for steps
Height	3.20m	

